

Key Features On All Models

- X-TORQ® Engine produces more power and torque, reduces emissions 75% and increases fuel economy 20%
- Smart Carb™ compensating carburetor produces full power in all cutting conditions
- Active Air Filtration with K&N Filter Wraps delivers cleanest air possible to carburetor in all cutting conditions and protects filter in wet cutting operations
- Momentary Contact ON/OFF Switch always "On" reduces flooding of engine
- DURASarter™ dust sealed starter and durable starter cord
- POLY-V Belt provides better power transmission, less re-tensioning and increased belt life
- Lightweight Magnesium Blade Guard for less operator fatigue and better control
- Reflective Labels for better visibility in the dark and smoke

Model	CE760 H¹	CE970 H¹	CE1260 H¹
ENGINE TYPE- X-TORQ®	Air cooled-2-stroke	Air cooled-2 stroke	Aircooled-2 stroke
DISPLACEMENT	4.5 cu in. (74cc)	5.7 cu in. (94cc)	7.3 cu in. (119cc)
MAXIMUM BLADE SPEED (No Load)	5400 RPM	5400 RPM	4700 RPM
POWER	5hp (3.7kW)	6.4hp (4.8kW)	7.8hp (5.8kW)
POWER/WEIGHT RATIO	24hp/23lbs .39kW/.33kg	28hp/25lbs .44kW/.41kg	28hp/24lbs .43kW/.40kg
SMART CARB™	Standard	Standard	Standard
MOMENTARY CONTACT ON/OFF SWITCH	Standard	Standard	Standard
COMPRESSION RELEASE	Standard	Standard	Standard
AIR PURGE	Standard	Standard	Standard
BIG GRIP "D" HANDLE	Standard	Standard	Standard
DURASarter™	Standard	Standard	Standard
FUEL LEVEL INDICATOR	Standard	Standard	Standard
ACTIVE AIR FILTRATION SYSTEM™	Standard	Standard	Standard
WATER KIT	Standard	Standard	Standard
MAGNESIUM BLADE GUARD	Standard	Standard	Standard
BLADE DIAMETER	12 in 305mm	14 in 355mm	16 in 400mm
CUTTING DEPTH	4 in 100mm	5 in 127mm	6 in 154mm
CUTTING BLADE (Standard)	Black Diamond Blade	Black Diamond Blade	Black Diamond Blade
REVERSIBLE CUTTING ARM	Standard	Standard	Standard
REPLACEABLE ARBOR BUSHING	Standard	Standard	Standard
POLY-V Belt	Standard	Standard	Standard
ARBOR SIZE	1 in 2.54cm	1 in 2.54cm	1 in 2.54cm
REFLECTIVE LABELS	Standard	Standard	Standard
SCRENCN TOOL & HOLDER	Standard	Standard	Standard
WEIGHT WITHOUT FUEL and CUTTING EQUIPMENT	20.7 lbs 9.4kg	25.1 lbs 11.4kg	32 lbs 14.4kg
SOUND POWER LEVEL			
Lwa, dB(A)	113	114	118
SOUND PRESSURE LEVEL VIBRATIONS (m/s²)			
Front Handle Equivalent	3.2/46	4.3/39	4.9/5.1
Rear Handle Equivalent	3.0/5.0	4.7/44	6.3/5.2



P.O. Box 946 | 3855 23rd Street | Baker City, Oregon 97814 USA
 Toll Free (US /Canada): 1-(800) 433-3716
 Telephone: (541) 524-9999 International: +1-(541) 524-9999
 Fax: 1-(541) 524-9996 Fax: +1-(541) 524-9996
 Email: info@cuttersedge.com
www.cuttersedge.com

920 EPR 2

Cutters Edge®
 An ISO 9001 Certified Company
FIRE RESCUE SAWS

MULTI-CUT® H¹ Series Rotary Rescue Saws

See The X-Torq® Engine in Action Now

"NEXT GENERATION TECHNOLOGY"
MULTI-CUT® H' Series Rotary Rescue Saws

Cutters Edge MULTI-CUT® Fire Rescue Saws are engineered and built specifically for the Fire Rescue Service to deliver 100% reliable high performance cutting in the extreme conditions of the fire rescue environment. All engines are EPA compliant, UL®, CE and ANSI approved.

This new X TORQ® technology utilizes Dual Intakes that split the airflow into one fresh-air stream and one clean-air stream for the fuel-air mixture. The fresh-air intake forms a barrier that delays the fresh fuel mix from entering the engine while assisting in exhausting the burned gases. Then the fuel-air mixture enters the engine, resulting in more power, higher torque, 75% less emissions and 20% more fuel economy than conventional 2-stroke engines.



Cutters Edge - U.S. / Canada: 1-800-433-3716 • International: +1 (541) 524-9999

Fax: 1 (541) 524-9996 • Email: info@cuttersedge.com • www.cuttersedge.com

For further info and price quote, please contact:

MDI-Canada

21 Deepglade Cr. Toronto, Ontario, M2J 2B3, Canada
Tel: 1-416-916-1558, 1-416-302-8431 Fax: 1-416-916-1666
Email: sales@mdicanada.ca, mdicanada@rogers.com
Website: www.mdicanada.ca